








SURFACE PROTECTION TAPE - 810-0

Surface Protection Tape 81000 series is a high performance tape based on polyethylene for protection of objects from scratches, oil stains and other impurities during transit. Specifically designed adhesive system suitable for Automotive Plastic parts like Bumpers, IP, Door Pads. The film has been designed specifically for Flaming operations prior to Plastic Part Painting, and sustain the Oven Temperatures upto 110°C for continuous 3 days. Typically available in Self Wound pattern.

TECHNICAL DATA.

Film		PE Triple Layered
Film Thickness		98-102 μ
Adhesive		Proprietary
Colour		Transparent
Adhesion to Steel -20mins		235 - 255 gms/inch
Adhesive Thickness		18 gsm
Application Temperature		+10 to +30 °C
Service Temperature		-40 to +110 °C

Features:

- Specially formulated adhesive designed to solvent-resistance
- Very good resistance to alcohols, mild detergents, etc
- No adhesive built up after application of the tape ensuring same peeling/removing force
- Passes Thermal Cycle 'C' as per Tata Specification TS 75006
- Designed to sustain a temperature of 110°C continuous for 3 days in case of Oven Overshoot without any change in performance

Auraa Adhesive Tapes Pvt Ltd warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user stores the material in the original boxes (out of direct sunlight) from our factory. We also recommend to store our material at 21°C with 50% relative humidity. Auraa Adhesive Tapes Pvt Ltd only warrants our products to be free from defects in workmanship or defects in Auraa material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by the seller or manufacturer. User assumes all risk and liability in connection herewith